

Android Quick Reference Card

iOS Quick Reference Card

Rev. 1

Note: Not all android Devices are created Equal, Please try your device before purchasing
 DigiFarms John Deere Solution is NOT supported on Android Devices.



Fig. 1



Fig. 2

Step 1: Pair the Beacon with android device. (fig. 1)

Step 2: Download DigiFarm app, Open it and select the gear in the top right corner (fig. 2)




Fig. 3




Fig. 4

Step 3: Select receiver settings(fig. 3) then Receiver connection(fig. 4), External via Bluetooth(fig. 5), then choose Bluetooth device(fig. 6), check auto-enable Bluetooth box (fig. 7)




Fig. 5




Fig. 6





Fig. 7

Step 4: Go back and select NTRIP Settings(Fig. 8), Network protocol NTRIP v1.0, Caster Port 3101, your username and password from DigiFarm , download source table, and get from external receiver.(fig. 9)



Step 5: return to the home screen of the app and push Connect. A list of mountpoints will appear for you to select the correct one. Once selected the app will start automatically.





Fig. 1




Fig. 2

Step 1: Pair the Beacon with the iOS device via the settings app. (Fig. 1 & 2)




Fig. 3

Step 2: Download the DigiFarm app and allow notifications. (Fig. 3)

Step 3: Confirm Beacon connection within the app(Fig. 4), Select your receiver type(Fig. 4), and enter your username and password. (Fig. 5)




Fig. 4




Fig. 5

Step 4: Press the green Start button, you will be prompted to allow location access. Allow this (Fig. 6) and you will start streaming RTK data. (Fig. 7)



Fig. 6




Fig. 7

DigiFarm Technical support
 (319)531-7574
 support@godigifarm.com